

Resistance / Potentiometer Transmitter

Product features

- Resistance / potentiometer inputs
- 3 or 4 wire measurement
- 0-10000 ohm measurement ranges
- Two wire 4-20 mA transmitter
- 0.05% accuracy
- TS-35 rail mounting, 12.5 mm width



Type Designation

DT1005 I4



Range [ohm]*				
0-50	0-100	0-120	0-130	0-150
0-180	0-200	0-250	0-270	0-300
0-470	0-500	0-700	0-800	0-1000
0-2000	0-5000	0-10000	--	--

* Other ranges for customer request also available

The **DT1005 I4 Resistance / Potentiometer Transmitter** provide a 4-20 mA signal in proportional to the resistance / potentiometer connected to their input. The device is loop-powered from 4-20 mA signal.

The resistance / potentiometer can be connect in 3 or 4 wire measuring mode.

The input ranges are fix configured, see on the above table. Different ranges for customer request also available.

Input and output is not isolated.

Input parameters:

Input signal:	resistance / potentiometer
Measurement range:	see the table on the previous page
Connection:	3 or 4 wire
Measuring current:	depends on the measuring range
Wire resistance:	100 ohm (max)

Kimeneti jellemzők:

Output signal:	4-20 mA
Overloading:	22 mA
Error:	< 0.05% + 10 µA (Tk: 23 °C ±2 °C) < 0.25% + 50 µA (Tk: 0 °C - +60 °C)

Supply-voltage effect:	practically zero
------------------------	------------------

Power supply:

Supply voltage:	10-30 VDC loop-powered
-----------------	------------------------

Ambient conditions:

Operating temperature range:	0-50°C (-20-50°C for customer request)
Relative humidity:	90% (max., non-condensing)
Place of installation:	cabinet

Electromagnetic compatibility (EMC)

accordance with the standard EN 61326:2000:

Immunity:	-B- criterion
Noise emission	-A- class

General data:

Housing:	terminal assembly box, rail mounting on TS-35 rail, material: polyamide PA6.6
Connection:	screw terminal
Connection cable:	0.25-2.5 mm ²
Dimensions:	12.5 x 99 x 115 mm (width x height x depth)
Weight:	0.1 kg
Protection:	IP 20

Detailed information see in operating instructions. The Manufacturer maintains the right to change the technical data!